

# Product specification sheet

Revision dated 20 September 2019

1.	Product code	GS001*																																					
2.	Product description	Unicare Latex																																					
3.	Material	Latex																																					
4.	Inspection parameters	<table border="1"> <thead> <tr> <th>Criteria</th> <th>Inspection level</th> <th>AQL</th> <th>Standard</th> </tr> </thead> <tbody> <tr> <td>Dimensions</td> <td>S-2</td> <td>4.0</td> <td>EN455-2</td> </tr> <tr> <td>Physical properties</td> <td>S-2</td> <td>4.0</td> <td>EN455-2</td> </tr> <tr> <td>Water tight test (1,000ml)</td> <td>G-1</td> <td>1.5</td> <td>EN455-1</td> </tr> <tr> <td>Visual defects</td> <td>G-1</td> <td>2.5</td> <td>In-house</td> </tr> </tbody> </table>									Criteria	Inspection level	AQL	Standard	Dimensions	S-2	4.0	EN455-2	Physical properties	S-2	4.0	EN455-2	Water tight test (1,000ml)	G-1	1.5	EN455-1	Visual defects	G-1	2.5	In-house									
Criteria	Inspection level	AQL	Standard																																				
Dimensions	S-2	4.0	EN455-2																																				
Physical properties	S-2	4.0	EN455-2																																				
Water tight test (1,000ml)	G-1	1.5	EN455-1																																				
Visual defects	G-1	2.5	In-house																																				
5.	Glove dimensions	<table border="1"> <thead> <tr> <th rowspan="2">Dimensions</th> <th colspan="5">Size (mm)</th> </tr> <tr> <th>XS</th> <th>S</th> <th>M</th> <th>L</th> <th>XL</th> </tr> </thead> <tbody> <tr> <td>Product code</td> <td>GS0011</td> <td>GS0012</td> <td>GS0013</td> <td>GS0014</td> <td>GS0015</td> </tr> <tr> <td>Palm width</td> <td>≤80</td> <td>80 ± 10</td> <td>95 ± 10</td> <td>110 ± 10</td> <td>≥ 110</td> </tr> <tr> <td>Length</td> <td>≥ 240</td> <td>≥ 240</td> <td>≥ 240</td> <td>≥ 240</td> <td>≥ 240</td> </tr> </tbody> </table>									Dimensions	Size (mm)					XS	S	M	L	XL	Product code	GS0011	GS0012	GS0013	GS0014	GS0015	Palm width	≤80	80 ± 10	95 ± 10	110 ± 10	≥ 110	Length	≥ 240	≥ 240	≥ 240	≥ 240	≥ 240
Dimensions	Size (mm)																																						
	XS	S	M	L	XL																																		
Product code	GS0011	GS0012	GS0013	GS0014	GS0015																																		
Palm width	≤80	80 ± 10	95 ± 10	110 ± 10	≥ 110																																		
Length	≥ 240	≥ 240	≥ 240	≥ 240	≥ 240																																		
6.	Glove thickness	<table border="1"> <thead> <tr> <th>Point of thickness measurement</th> <th>Nominal single wall (mm)</th> </tr> </thead> <tbody> <tr> <td>Cuff (at beaded end)</td> <td>0.08</td> </tr> <tr> <td>Palm (at centre of palm)</td> <td>0.10</td> </tr> <tr> <td>Fingertip (at fingertip)</td> <td>0.12</td> </tr> </tbody> </table>									Point of thickness measurement	Nominal single wall (mm)	Cuff (at beaded end)	0.08	Palm (at centre of palm)	0.10	Fingertip (at fingertip)	0.12																					
Point of thickness measurement	Nominal single wall (mm)																																						
Cuff (at beaded end)	0.08																																						
Palm (at centre of palm)	0.10																																						
Fingertip (at fingertip)	0.12																																						
7.	Physical properties	<table border="1"> <thead> <tr> <th>Parameters</th> <th>Before aging</th> <th>After aging</th> </tr> </thead> <tbody> <tr> <td>Median force at break (N)</td> <td>Min 6.0</td> <td>N/A</td> </tr> <tr> <td>Tensile strength (MPa)</td> <td>Min 18.0</td> <td>Min 14.0</td> </tr> <tr> <td>Ultimate elongation (%)</td> <td>Min 650</td> <td>Min 500</td> </tr> </tbody> </table>									Parameters	Before aging	After aging	Median force at break (N)	Min 6.0	N/A	Tensile strength (MPa)	Min 18.0	Min 14.0	Ultimate elongation (%)	Min 650	Min 500																	
Parameters	Before aging	After aging																																					
Median force at break (N)	Min 6.0	N/A																																					
Tensile strength (MPa)	Min 18.0	Min 14.0																																					
Ultimate elongation (%)	Min 650	Min 500																																					
8.	Proteins	< 50 µg/g extractable latex proteins																																					
9.	Powder residue	Maximum 2.0 mg / glove																																					
10.	Cuff type	Beaded																																					
11.	Design	Ambidextrous																																					
12.	Surface	Microroughened																																					
13.	Colour	Natural																																					
14.	Quality assurance	Manufactured under ISO 9001 and ISO 13485																																					
15.	Weight (size medium)	5.7g																																					
16.	Standards compliant with	EN455-1	EN455-2	EN455-3	EN455-4	EN420	EN374-1	EN374-2	EN374-4	EN374-5	Food approved																												
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓																												

The above data represents the product norm, which may be changed without notice and is intended as a guide only.