

Product specification sheet

Revision 4 | 17 October 2017

1.	Product code	GS021*																												
2.	Product description	Unicare Flex Blue Nitrile powder free 100s																												
3.	Material	Nitrile																												
4.	Inspection parameters	<table border="1"> <thead> <tr> <th>Criteria</th> <th>Inspection level</th> <th>AQL</th> <th colspan="2">Standard</th> </tr> </thead> <tbody> <tr> <td>Dimensions</td> <td>S-2</td> <td>4</td> <td colspan="2">EN455-2</td> </tr> <tr> <td>Physical properties</td> <td>S-2</td> <td>4</td> <td colspan="2">EN455-2</td> </tr> <tr> <td>Water tight test (1,000ml)</td> <td>G-1</td> <td>4</td> <td colspan="2">EN455-1</td> </tr> <tr> <td>Visual defects</td> <td>G-1</td> <td>2.5</td> <td colspan="2">In-house</td> </tr> </tbody> </table>				Criteria	Inspection level	AQL	Standard		Dimensions	S-2	4	EN455-2		Physical properties	S-2	4	EN455-2		Water tight test (1,000ml)	G-1	4	EN455-1		Visual defects	G-1	2.5	In-house	
Criteria	Inspection level	AQL	Standard																											
Dimensions	S-2	4	EN455-2																											
Physical properties	S-2	4	EN455-2																											
Water tight test (1,000ml)	G-1	4	EN455-1																											
Visual defects	G-1	2.5	In-house																											
5.	Glove dimensions	<table border="1"> <thead> <tr> <th rowspan="2">Dimensions</th> <th colspan="4">Size (mm)</th> </tr> <tr> <th>S</th> <th>M</th> <th>L</th> <th>XL</th> </tr> </thead> <tbody> <tr> <td>Product code</td> <td>GS0212</td> <td>GS0213</td> <td>GS0214</td> <td>GS0215</td> </tr> <tr> <td>Palm width</td> <td>80 ± 10</td> <td>95 ± 10</td> <td>110 ± 10</td> <td>≥ 110</td> </tr> <tr> <td>Length</td> <td>≥ 240</td> <td>≥ 240</td> <td>≥ 240</td> <td>≥ 240</td> </tr> </tbody> </table>				Dimensions	Size (mm)				S	M	L	XL	Product code	GS0212	GS0213	GS0214	GS0215	Palm width	80 ± 10	95 ± 10	110 ± 10	≥ 110	Length	≥ 240	≥ 240	≥ 240	≥ 240	
Dimensions	Size (mm)																													
	S	M	L	XL																										
Product code	GS0212	GS0213	GS0214	GS0215																										
Palm width	80 ± 10	95 ± 10	110 ± 10	≥ 110																										
Length	≥ 240	≥ 240	≥ 240	≥ 240																										
6.	Glove thickness	<table border="1"> <thead> <tr> <th>Point of thickness measurement</th> <th>Nominal single wall (mm)</th> </tr> </thead> <tbody> <tr> <td>Cuff (at beaded end)</td> <td>0.04</td> </tr> <tr> <td>Palm (at centre of palm)</td> <td>0.05</td> </tr> <tr> <td>Fingertip (at fingertip)</td> <td>0.06</td> </tr> </tbody> </table>				Point of thickness measurement	Nominal single wall (mm)	Cuff (at beaded end)	0.04	Palm (at centre of palm)	0.05	Fingertip (at fingertip)	0.06																	
Point of thickness measurement	Nominal single wall (mm)																													
Cuff (at beaded end)	0.04																													
Palm (at centre of palm)	0.05																													
Fingertip (at fingertip)	0.06																													
7.	Physical properties	<table border="1"> <thead> <tr> <th>Parameters</th> <th>Before aging</th> <th>After aging</th> </tr> </thead> <tbody> <tr> <td>Median force at break (N)</td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>Tensile strength (MPa)</td> <td>Min 14.0</td> <td>Min 14.0</td> </tr> <tr> <td>Ultimate elongation (%)</td> <td>Min 500</td> <td>Min 400</td> </tr> </tbody> </table>				Parameters	Before aging	After aging	Median force at break (N)	N/A	N/A	Tensile strength (MPa)	Min 14.0	Min 14.0	Ultimate elongation (%)	Min 500	Min 400													
Parameters	Before aging	After aging																												
Median force at break (N)	N/A	N/A																												
Tensile strength (MPa)	Min 14.0	Min 14.0																												
Ultimate elongation (%)	Min 500	Min 400																												
8.	Proteins	None																												
9.	Powder residue	Maximum 2.0 mg / glove																												
10.	Cuff type	Beaded																												
11.	Design	Ambidextrous																												
12.	Surface	Fingertip textured																												
13.	Colour	Blue																												
14.	Quality assurance	Manufactured under ISO 9001 and 13485																												
15.	Weight (based on size medium)	2.2g																												

The above data represents the product norm, which may be changed without notice and is intended as a guide only.